Section 1 - IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY

Product Identifier CASKADE ULTRASHIELD 3000 AEROSOL – ALL SCENTS

Product Code C5003000

Recommended use Air care products, Odour agents.

Manufacturer/Supplier Integra Industries Limited

Address 149 King Edward Street

South Dunedin, NZ

Telephone 0800 667 843

Email <u>info@integraindustries.co.nz</u>

Emergency Phone No National Poisons Centre 0800 764 766 (0800 POISON) 24 hours

Section 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.

Classified as a dangerous goods for transport purposes.

HSNO Classifications: GHS Classifications:

2.1.2AExtremely flammable aerosolFlammable aerosolCategory 16.3BMildly irritating to the skinSkin IrritationCategory 36.4AIrritating to the eyeEye irritationCategory 2B

Pictograms



Signal Words: Danger

Hazard Statement Codes

H222 Extremely flammable aerosol.
 H316 Causes mild skin irritation.
 H320 Causes eye irritation.

Section 3 - COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
2-Propanol	67-63-0	> 60
Didecyl Dimethyl Ammonium Chloride	7173-51-5	< 2
Hydrocarbon propellant (LPG - propane, butane)	68476-85-7	20 - 40
Other ingredients determined to not be hazardous	-	to 100%

Ref: ULTRASHIELD 3000 AEROSOL Date: 18.4.20 Supersedes: New Issue No: 1 Page 1 of 5 pages

Section 4 - FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

Call a POISON CENTRE (0800 764 766) or doctor if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. If eye irritation persists: Get medical advice.

Skin contact IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice.

Inhalation IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.

Ingestion Ingestion is unlikely to occur with product packaging. If swallowed, do NOT induce vomiting. Obtain

immediate medical attention.

Exposure symptoms Prolonged and repeated exposure may cause Irritant effects. Symptoms may include defatting of the

skin and dermatitis.

Notes to physician Provide general supportive measures and treat symptomatically.

Section 5 - FIRE-FIGHTING MEASURES

Specific hazards Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an

explosive mixture with air. Vapours can travel to a source of ignition and flash back. Contents may float

and be re-ignited on surface water.

Further advice On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters

to wear self-contained breathing apparatus if risk of exposure to products of combustion. Use water

spray to keep fire-exposed containers cool.

Extinguishing media For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.

For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water

may be ineffective. Do not discharge extinguishing waters into the aquatic environment.

Do NOT use straight streams of water.

Hazchem Code 2YE

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions Clean up immediately. Remove all sources of ignition. Provide ventilation. Keep unnecessary and

unprotected personnel out of the area. Wear appropriate personal protective equipment.

Environmental Precautions If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until

pressure has dissipated. Undamaged cans should be gathered and stowed safely. Prevent entry of split

material into drains or water courses. If material enters drains, advise emergency services.

disposal. Wash area down with excess water. Clean up in accordance with all applicable regulations.

Section 7 - HANDLING AND STORAGE

Handling Precautions Read product label before use. Keep out of reach of children.

This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even

after use.

Use outdoors or in well-ventilated area. Avoid breathing spray. Wash hands with soap and water after

handling. In case of inadequate ventilation wear respiratory protection.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool,

dry place. Keep away from heat, sparks, and flame. Store locked up.

Ref: ULTRASHIELD 3000 AEROSOL Date: 18.4.20 Supersedes: New Issue No: 1 Page 2 of 5 pages

Section 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m ³	STEL, mg/m ³
Ethanol	1880	-
LPG (Liquefied petroleum gas		
butane, propane)	1800	

Additional Information Wash hands before eating, drinking smoking and using the lavatory and at the end of the working

period.

Engineering Controls No controls required when handling small quantities. Use with adequate ventilation.

Larger quantities: General exhaust is adequate under normal operating conditions. Ventilation equipment should be explosion-resistant. De-energise electrical equipment before using.

Protective Equipment In an industrial environment: gloves, safety glasses or chemical goggles are recommended. Wash

contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. In case of inadequate ventilation wear respiratory protection. If TWA is exceeded,

wear an approved respirator with a type A filter.

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state

Odour

Characteristic odour.

PH

Not applicable.

Vapour Density

Vapour Pressure, kPa

Clear, colourless liquid.

Not applicable.

> 1 (Air = 1)

300 - 600

Boiling Point, °C

Melting Point, °C

Not applicable.

Specific Gravity

Not applicable.

Flash Point, °C

Explosion Limit, % v/v

Autoignition Temp, °C

Not applicable.

Not applicable.

Not applicable.

Not applicable

Section 10 – STABILITY AND REACTIVITY

Solubility

Stability Stable under normal conditions of use and storage. Not reactive. Avoid oxidisers. Hazardous

polymerisation will not occur.

Miscible with water.

Section 11 - TOXICOLOGICAL INFORMATION

Health Hazard Summary This product may have the potential to cause adverse health effects. Use safe work practices to avoid

eye and skin contact and inhalation.

Basis for Assessment Information given is based on product testing, and/or similar products, and/or components.

Acute Oral Toxicity Low toxicity: LD_{50} estimated to be > 5,000 mg/kg (based on component mixture rules).

Acute Dermal Toxicity Low toxicity: LD_{50} estimated to be > 5,000 mg/kg (based on component mixture rules).

Acute Inhalation Toxicity Low toxicity: LD_{50} estimated to be > 20 mg/L (based on component mixture rules).

Ingestion May be harmful. Ingestion of large quantities may result in nausea and vomiting.

Skin Irritation Prolonged/repeated contact may cause irritation and defatting of the skin which can lead to dermatitis.

Ref: ULTRASHIELD 3000 AEROSOL Date: 18.4.20 Supersedes: New Issue No: 1 Page 3 of 5 pages

Sensitisation Product is not expected to be a contact and respiratory sensitiser.

Eye Irritation Direct contact is irritating to the eye. Expected to be temporary.

Respiratory Irritation Inhalation of mists may cause irritation to the respiratory system.

Repeated Dose Toxicity Repeated and prolonged contact with product may result in irritant dermatitis.

Additional Information None of the components present in this material at concentrations equal to or greater than 0.1% are

listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

Section 12 – ECOTOXICITY INFORMATION

Ecotoxicity Slightly harmful in the aquatic environment. However, this does not exclude the possibility that large

spills can have a harmful or damaging effect on the environment.

Mobility: Product is volatile and will rapidly evaporate to the air.

Persistence/degradability Expected to rapidly biodegrade.

Bioaccumulation Not expected to bioaccumulate.

Section 13 – DISPOSAL CONSIDERATIONS

Material Disposal Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into

the environment, in drains or in water courses. Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an

authorised facility is suggested.

Container Disposal Recycle empty container if possible. Product containers are also considered wastes of the same class of

the contents and should be disposed of in accordance with applicable regulations.

Section 14 - TRANSPORT INFORMATION

Transport Classified as a Dangerous Good for transport purposes.

Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7.

They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.

Proper Shipping Name Aerosols
UN Number 1950
Dangerous Goods Class 2.1

Transport Labels Required Class 2 Flammable



Subsidiary Risk Not applicable

Packing Group Not applicable

Marine Pollutant No

EMS Number F-D, S-U

DG Segregation This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous

Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

Section 15 - REGULATORY INFORMATION

SDS regulations Prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.

Inventory ListingAll components of this product are listed on the New Zealand Inventory of Chemicals (NZIoC).

Ref: ULTRASHIELD 3000 AEROSOL Date: 18.4.20 Supersedes: New Issue No: 1 Page 4 of 5 pages

Approved Handler: 2.1.2A - Required for quantities greater than 3,000 litres (aggregate water capacity).

Location Test Certificate: 2.1.2A - Required for quantities greater than 3,000 litres (aggregate water capacity).

Tracking: This substance is not a tracked substance.

EPA Approval Number HSR002515 Aerosols (Flammable) Group Standard 2017.

EPA Hsno Controls: Refer to www.epa.govt.nz for information on Controls.

This substance is to be managed using the conditions specified in an applicable Group Standard.

Section 16 – OTHER INFORMATION

Additional information

Personal Protective Equipment Guidelines:

The recommendation for protective equipment contained is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and engineering controls should be considered before final selection of personal protective equipment is made.

Health Effects from Exposure:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. It is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

AICS Australian Inventory of Chemical Substances

ADG Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Chemical Abstract Service number

EMS Emergency Response Procedures for Ships Carrying Dangerous Goods

EPA Environmental Protection Agency (New Zealand)

GHS Globally Harmonized System

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC₅₀ Lethal Concentration, 50% / Median Lethal Concentration

LD₅₀ Lethal Dose, 50% / Median Lethal Dose

LEL Lower Explosion Limit mg/m³ Milligrams per Cubic Metre

NICNAS National Industrial Chemicals Notification and Assessment Scheme (Australia)

NZIoC New Zealand Inventory of Chemicals

N.O.S. Not otherwise specified
 OEL Occupational Exposure Limit
 PEL Permissible Exposure Limit
 STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

TLV Threshold Limit Value
TWA Time Weighted Average
UEL Upper Explosion Limit

The information contained in this Safety Data Sheet is provided in good faith and is believed to be correct as at the date hereof. However, it is expected that individuals receiving the information will exercise their independent judgement in determining it's appropriateness for a particular purpose. The Proprietor makes no representation as to the accuracy or comprehensiveness of the information. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of the use of the product are therefore assumed by the user and we expressly disclaim all warranties of any kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product. Appropriate warnings and safe handling procedures should be provided to handlers and users.

Ref: ULTRASHIELD 3000 AEROSOL Date: 18.4.20 Supersedes: New Issue No: 1 Page 5 of 5 pages