

Safety Data Sheet

Copyright,2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-0352-6	Version number:	2.01
Issue Date:	2020/10/21	Supercedes Date:	2018/02/16

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification	
1.1. Product identifier	
Scotchgard TM Rug & Carnet Protector (Cat. No. 4406-17, 4406-14)	

Scotchgard[™] Rug & Carpet Protector (Cat. No. 4406-17, 4406-14)

Product Identification Numbers

70-0050-7525-7 70-0050-7526-5 70-0051-3371-8 70-0052-5207-0 70-0068-4614-4 LN-0000-1469-2

1.2. Recommended use and restrictions on use

Intended Use Water, oil and stain protector for carpet and rug

Restrictions on use Not applicable

1.3. Supplier's details

Company:	3M Canada Company	
Division:	Home Care Division	
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario	N6A 4T1
Telephone:	(800) 364-3577	
Website:	www.3M.ca	

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

The following product identification number(s) are sold in the consumer market place: 70-0068-4614-4

2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1. Gas Under Pressure: Liquefied gas. Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements Signal word Danger

Symbols Flame | Gas cylinder | Health Hazard |

Pictograms



Hazard statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Causes damage to organs: cardiovascular system |

Precautionary statements General:

Keep out of reach of children.

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

Response:

IF exposed or concerned: Call a POISON CENTRE or doctor/physician.

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

2.3. Other hazards

None known.

15% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Water	7732-18-5	83 - 90	Water
Isobutane	75-28-5	5 - 10	Propane, 2-methyl-
Fluorochemical Urethane	Trade Secret	3 - 7	Not Applicable
PETROLEUM GASES,	68476-86-8	1 - 5	Petroleum gases, liquefied, sweetened
LIQUEFIED, SWEETENED			

Benzenesulfonic acid, dodecyl-,	69227-09-4	< 0.20	Benzenesulfonic acid, dodecyl-, branched,
branched, sodium salt			sodium salt
Morpholine	110-91-8	< 0.20	Morpholine

Fluorochemical Urethane is a non-hazardous Trade Secret material according to WHMIS criteria.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Wash with soap and water. If you feel unwell, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

Substance	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Fluoride	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or

exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

C.A.S. No.	Agency	Limit type	Additional Comments
110-91-8	ACGIH	TWA:20 ppm	Danger of cutaneous
			absorption
75-28-5	ACGIH	STEL:1000 ppm	
75-28-5	ACGIH	Limit value not established:	simple asphyxiant
	110-91-8 75-28-5	110-91-8 ACGIH 75-28-5 ACGIH	110-91-8 ACGIH TWA:20 ppm 75-28-5 ACGIH STEL:1000 ppm

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield Indirect Vented Goggles

Skin/hand protection

No protective gloves required.

Respiratory protection

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid		
Specific Physical Form:	Aerosol		
Colour	White		
Odour	Slight Solvent		
Odour threshold	No Data Available		
рН	9 [Details:(Liquid fill only)]		
Melting point/Freezing point	Not Applicable		
Boiling point	100 °C		
Flash Point	No flash point		
Evaporation rate	No Data Available		
Flammability (solid, gas)	Not Applicable		
Flammable Limits(LEL)	No Data Available		
Flammable Limits(UEL)	No Data Available		
Vapour Pressure	No Data Available		
Viscosity/Kinematic Viscosity Viscosity/Kinematic	No Data Available		
Viscosity			
Density	1 g/ml		
Relative density	Approximately 1 [<i>Ref Std</i> :WATER=1] [<i>Details:</i> (Liquid fill		
	only)]		
Water solubility			
Solubility- non-water	No Data Available		
Partition coefficient: n-octanol/ waterNo Data Available			
utoignition temperature Not Applicable			
Decomposition temperature	No Data Available		
Viscosity/Kinematic Viscosity	No Data Available		
Volatile Organic Compounds	Approximately 10.2 % weight [Details:10.2 new formulation,		
	9.45 old formulation]		
Percent volatile	Approximately 94.5 % weight		
VOC Less H2O & Exempt Solvents			

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous reactions Hazardous polymerization will not occur.

10.4. Conditions to avoid None known.

10.5. Incompatible materials None known.

10.6. Hazardous decomposition products

Substance

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

Condition

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

No known health effects.

Additional Health Effects:

Single exposure may cause target organ effects:

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isobutane	Inhalation- Gas (4 hours)	Rat	LC50 276,000 ppm
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation- Gas (4 hours)	Rat	LC50 277,000 ppm
Morpholine	Dermal	Rabbit	LD50 310 mg/kg
Morpholine	Inhalation- Vapor	Rat	LC50 estimated to be 10 - 20 mg/l
Morpholine	Ingestion	Rat	LD50 1,050 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Isobutane	Professio	No significant irritation
	nal	
	judgeme	
	nt	
PETROLEUM GASES, LIQUEFIED, SWEETENED	Professio	No significant irritation
	nal	-
	judgeme	
	nt	
Morpholine	official	Corrosive
	classifica	
	tion	

Serious Eye Damage/Irritation

Name	Species	Value
Isobutane	Professio	No significant irritation
	nal	
	judgeme	
	nt	
PETROLEUM GASES, LIQUEFIED, SWEETENED	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Morpholine	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Morpholine	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isobutane	In Vitro	Not mutagenic
PETROLEUM GASES, LIQUEFIED, SWEETENED	In Vitro	Not mutagenic
Morpholine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Morpholine	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Morpholine	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Morpholine	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation	cardiac sensitization	Causes damage to organs	similar compoun ds	NOAEL Not available	
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation	respiratory irritation	Not classified		NOAEL Not available	
Morpholine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
PETROLEUM GASES, LIQUEFIED, SWEETENED	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL Not available	
Morpholine	Dermal	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	LOAEL 900 mg/kg/day	13 days
Morpholine	Dermal	hematopoietic system	Not classified	Guinea pig	NOAEL 900 mg/kg/day	13 days
Morpholine	Inhalation	eyes	Causes damage to organs through	Human	NOAEL Not	occupational

			prolonged or repeated exposure		available	exposure
Morpholine	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.09 mg/l	13 weeks
Morpholine	Inhalation	liver kidney and/or bladder	Not classified	Rat	LOAEL 64 mg/l	5 days
Morpholine	Inhalation	heart endocrine system	Not classified	Rat	NOAEL 0.9 mg/l	13 weeks
Morpholine	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 0.53 mg/l	104 weeks
Morpholine	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 160 mg/kg/day	30 days
Morpholine	Ingestion	liver respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 160 mg/kg/day	30 days
Morpholine	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 800 mg/kg/day	30 days
Morpholine	Ingestion	endocrine system	Not classified	Rat	NOAEL 323 mg/kg/day	4 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in

compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 4 Instability: 0 Special Hazards: None Aerosol Storage Code: 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard ClassificationHealth:4Flammability:4Physical Hazard:0Personal Protection:X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	28-0352-6	Version number:	2.01
Issue Date:	2020/10/21	Supercedes Date:	2018/02/16

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca