



A Solenis Company

# Safety Data Sheet

## TASKI TAPI DEFOAM

Revision: 2023-11-30

Version: 01.1

### SECTION 1: Identification of the substance/mixture and supplier

#### 1.1 Product identifier

**Product name:** TASKI TAPI DEFOAM

#### 1.2 Recommended use and restrictions on use

##### Restrictions of use:

Uses other than those identified are not recommended

#### 1.3 Details of the supplier

DIVERSEY NEW ZEALAND LTD.

24 Bancroft Crescent, Glendene, Auckland, 0602, New Zealand

Telephone: 0800 803 615 (toll free)

Website: [www.diversey.com](http://www.diversey.com)

#### 1.4 Emergency telephone number

Seek medical advice (show the label or safety data sheet where possible)

Call 0800 243 622 (24 hrs)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Flammable liquids, Category 2

Acute toxicity, oral, Category 5

Skin irritation, Category 3

Eye irritation, Category 2

#### 2.2 Label elements



**Signal word:** Danger

#### Hazard statements:

H225 - Highly flammable liquid and vapour.

H303 - May be harmful if swallowed.

H316 - Causes mild skin irritation.

H319 - Causes serious eye irritation.

#### Prevention statement(s):

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P264 - Wash face, hands and any exposed skin thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing and eye or face protection.

#### Response statement(s):

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## TASKI TAPI DEFOAM

P337 + P313 - If eye irritation persists: Get medical advice or attention.  
 P312 - Call a POISON CENTRE, doctor or physician if you feel unwell.  
 P363 - Wash contaminated clothing before reuse.  
 P370 + P378 - In case of fire: Use chemical powder to extinguish.

**Storage statement(s):**

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 - Store in a well-ventilated place. Keep cool.  
 P405 - Store locked up.

**Disposal statement(s):**

P501 - Dispose of unused content as chemical waste.

**2.3 Other hazards**

No other hazards known.

**SECTION 3: Composition/information on ingredients****3.1 Substances / Mixtures**

Ingredient(s)	CAS#	EC number	Weight percent
Propan-2-ol	67-63-0	200-661-7	>= 60

[4] Polymer.

Non-hazardous ingredients are the remainder and add up to 100%.

Workplace exposure limit(s), if available, are listed in subsection 8.1.

**SECTION 4: First aid measures****4.1 Description of first aid measures****Inhalation:**

Remove person to fresh air and keep comfortable for breathing.

**Skin contact:**

Take off immediately all contaminated clothing and wash it before reuse.

**Eye contact:**

Hold eyelids apart and flush eyes with plenty of lukewarm water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation occurs and persists, get medical attention.

**Ingestion:**

Rinse mouth. Immediately drink 1 glass of water. Never give anything by mouth to an unconscious person. Get medical attention or advice if you feel unwell.

**Self-protection of first aider:**

Consider personal protective equipment as indicated in subsection 8.2.

**First aid facilities:**

Eyewash facilities should be considered in a workplace where necessary.

**4.2 Most important symptoms and effects, both acute and delayed****Inhalation:**

May cause drowsiness or dizziness.

**Skin contact:**

No known effects or symptoms in normal use.

**Eye contact:**

Causes severe irritation.

**Ingestion:**

No known effects or symptoms in normal use.

**4.3 Indication of any immediate medical attention and special treatment needed**

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

**Poison Information Center:** Call 0800 764 766 (0800 POISON)

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Carbon dioxide. Dry powder. Water spray jet. Fight larger fires with water spray jet or alcohol-resistant foam.

**5.2 Special hazards arising from the substance or mixture**

No special hazards known.

**5.3 Advice for firefighters**

As in any fire, wear self contained breathing apparatus and suitable protective clothing including gloves and eye/face protection.

**5.4 Hazchem code**

•2YE

•2 - Alcohol resistant foam is the preferred firefighting medium but, if it is not available, fine water spray can be used

Y - Full fire kit and breathing apparatus. Contain.

E - People should be warned to stay indoors with all doors and windows closed, but evacuation may need to be considered

## TASKI TAPI DEFOAM

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Turn off all sources of ignition. Ventilate the area. Ensure adequate ventilation. Do not breathe dust or vapour. Wear suitable protective clothing, gloves and eye/face protection.

**6.2 Environmental precautions**

Do not allow to enter drainage system, surface or ground water. Dilute with plenty of water.

**6.3 Methods and material for containment and cleaning up**

Absorb with liquid-binding material (sand, diatomite, universal binders). Ensure adequate ventilation.

**6.4 Reference to other sections**

For personal protective equipment see subsection 8.2. For disposal considerations see section 13.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Measures to prevent fire and explosions:**

Keep away from flames and hot surfaces. No smoking. Keep away from heat. Take precautionary measures against static discharges.

**Measures required to protect the environment:**

For environmental exposure controls see subsection 8.2.

**Advices on general occupational hygiene:**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Handle and open container with care. Do not mix with other products unless advised by Diversey. Wash hands before breaks and at the end of workday. Wash face, hands and any exposed skin thoroughly after handling. Take off immediately all contaminated clothing. Store used personal protective equipment separately. Avoid contact with skin and eyes. Do not breathe vapours. Use only with adequate ventilation. See chapter 8.2, Exposure controls / Personal protection.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in accordance with local and national regulations. Store in a well-ventilated place. Store in a closed container. Keep only in original packaging. Keep cool. Keep away from heat and direct sunlight.

For conditions to avoid see subsection 10.4. For incompatible materials see subsection 10.5.

**7.3 Specific end use(s)**

No specific advice for end use available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Workplace exposure limits**

Air limit values, if available:

Ingredient(s)	Long term value(s)	Short term value(s)	Ceiling value(s)
Propan-2-ol	400 ppm 983 mg/m <sup>3</sup>	500 ppm 1230 mg/m <sup>3</sup>	

Biological limit values, if available:

**8.2 Exposure controls**

*The following information applies for the uses indicated in subsection 1.2 of the Safety Data Sheet.*

*If available, please refer to the product information sheet for application and handling instructions.*

*Normal use conditions are assumed for this section.*

*Recommended safety measures for handling the undiluted product:*

**Appropriate engineering controls:**

The product is intended to be used in closed systems.

**Appropriate organisational controls:**

Avoid direct contact and/or splashes where possible. Train personnel.

**Personal protective equipment****Eye / face protection:**

Safety glasses or goggles (AS/NZS 1337.1).

**Hand protection:**

Chemical-resistant protective gloves (AS/NZS 2161.10). Verify instructions regarding permeability and breakthrough time, as provided by the gloves supplier. Consider specific local use conditions, such as risk of splashes, cuts, contact time and temperature.

Suggested gloves for prolonged contact: Material: butyl rubber Penetration time:  $\geq 480$  min Material thickness:  $\geq 0.7$  mm

Suggested gloves for protection against splashes: Material: nitrile rubber Penetration time:  $\geq 30$  min Material thickness:  $\geq 0.4$  mm

In consultation with the supplier of protective gloves a different type providing similar protection may

## TASKI TAPI DEFOAM

<b>Body protection:</b>	be chosen. Wear chemical-resistant clothing and boots in case direct dermal exposure and/or splashes may occur (EN 14605).
<b>Respiratory protection:</b>	Respiratory protection is not normally required. However, inhalation of vapour, spray, gas or aerosols should be avoided.
<b>Environmental exposure controls:</b>	Should not reach sewage water or drainage ditch undiluted or unneutralised.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

	Method / remark
<b>Physical state:</b> Liquid <b>Colour:</b> Clear , Colourless <b>Odour:</b> Product specific <b>Odour threshold:</b> Not applicable <b>pH:</b> Not available <b>Melting point/freezing point (°C):</b> Not determined <b>Initial boiling point and boiling range (°C):</b> Not determined	Not relevant to classification of this product
<b>Flammability (liquid):</b> Flammable. <b>Flash point (°C):</b> ≈ 14.5 °C <b>Sustained combustion:</b> Not applicable. <i>( UN Manual of Tests and Criteria, section 32, L.2 )</i>	closed cup
<b>Evaporation rate:</b> Not determined <b>Flammability (solid, gas):</b> Not applicable to liquids <b>Lower and upper explosion limit/flammability limit (%):</b> Not determined <b>Vapour pressure:</b> Not determined <b>Relative density:</b> ≈ 0.80 (20 °C) <b>Relative vapour density:</b> Not determined. <b>Particle characteristics:</b> No data available. <b>Solubility in / Miscibility with water:</b> Fully miscible <b>Partition coefficient: n-octanol/water</b> No information available.	Not relevant to classification of this product
Substance data, partition coefficient n-octanol/water (log Kow): see subsection 12.3	
<b>Autoignition temperature:</b> Not determined <b>Decomposition temperature:</b> Not applicable. <b>Viscosity:</b> Not determined <b>Explosive properties:</b> Not explosive. Vapours may form explosive mixtures with air. <b>Oxidising properties:</b> Not oxidising.	

**9.2 Other information**

**Surface tension (N/m):** Not determined  
**Corrosion to metals:** Not corrosive

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

**10.2 Chemical stability**

Stable under normal storage and use conditions.

**10.3 Possibility of hazardous reactions**

No hazardous reactions known under normal storage and use conditions.

**10.4 Conditions to avoid**

Take action to prevent static discharges.

**10.5 Incompatible materials**

None known under normal use conditions.

**10.6 Hazardous decomposition products**

None known under normal storage and use conditions.

**SECTION 11: Toxicological information**

## TASKI TAPI DEFOAM

## 11.1 Information on toxicological effects

Mixture data: .

## Relevant calculated ATE(s):

ATE - Oral (mg/kg): 3900

Substance data, where relevant and available, are listed below:.

## Acute toxicity

Acute oral toxicity

Ingredient(s)	Endpoint	Value (mg/kg)	Species	Method	Exposure time (h)
Propan-2-ol	LD <sub>50</sub>	5840	Rat	OECD 401 (EU B.1)	

Acute dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg)	Species	Method	Exposure time (h)
Propan-2-ol	LD <sub>50</sub>	> 2000	Rabbit	Method not given	

Acute inhalative toxicity

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
Propan-2-ol	LC <sub>50</sub>	> 25 (vapour)	Rat	OECD 403 (EU B.2)	6

## Irritation and corrosivity

Skin irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
Propan-2-ol	Not irritant	Rabbit	OECD 404 (EU B.4)	

Eye irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
Propan-2-ol	Irritant	Rabbit	OECD 405 (EU B.5)	

Respiratory tract irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
Propan-2-ol	No data available			

## Sensitisation

Sensitisation by skin contact

Ingredient(s)	Result	Species	Method	Exposure time (h)
Propan-2-ol	Not sensitising	Guinea pig	OECD 406 (EU B.6) / Buehler test	

Sensitisation by inhalation

Ingredient(s)	Result	Species	Method	Exposure time
Propan-2-ol	No data available			

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Mutagenicity

Ingredient(s)	Result (in-vitro)	Method (in-vitro)	Result (in-vivo)	Method (in-vivo)
Propan-2-ol	No evidence for mutagenicity, negative test results No evidence of genotoxicity, negative test results	OECD 471 (EU B.12/13)	No evidence of genotoxicity, negative test results	OECD 474 (EU B.12)

Carcinogenicity

Ingredient(s)	Effect
Propan-2-ol	No evidence for carcinogenicity, negative test results

Toxicity for reproduction

Ingredient(s)	Endpoint	Specific effect	Value (mg/kg bw/d)	Species	Method	Exposure time	Remarks and other effects reported
Propan-2-ol			No data				

## TASKI TAPI DEFOAM

			available				
--	--	--	-----------	--	--	--	--

**Repeated dose toxicity**

Sub-acute or sub-chronic oral toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
Propan-2-ol		No data available				

Sub-chronic dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
Propan-2-ol		No data available				

Sub-chronic inhalation toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
Propan-2-ol		No data available				

Chronic toxicity

Ingredient(s)	Exposure route	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time	Specific effects and organs affected	Remark
Propan-2-ol			No data available					

STOT-single exposure

Ingredient(s)	Affected organ(s)
Propan-2-ol	Central nervous system

STOT-repeated exposure

Ingredient(s)	Affected organ(s)
Propan-2-ol	No data available

**Aspiration hazard**

Substances with an aspiration hazard (H304), if any, are listed in section 3. If relevant, see section 9 for dynamic viscosity and relative density of the product.

**Potential adverse health effects and symptoms**

Effects and symptoms related to the product, if any, are listed in subsection 4.2.

**SECTION 12: Ecological information****12.1 Toxicity**

No data is available on the mixture.

Substance data, where relevant and available, are listed below:

**Aquatic short-term toxicity**

Aquatic short-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
Propan-2-ol	LC <sub>50</sub>	> 100	<i>Pimephales promelas</i>	Method not given	48

Aquatic short-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
Propan-2-ol	EC <sub>50</sub>	> 100	<i>Daphnia magna Straus</i>	Method not given	48

Aquatic short-term toxicity - algae

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
Propan-2-ol	EC <sub>50</sub>	> 100	<i>Scenedesmus quadricauda</i>	Method not given	72

Aquatic short-term toxicity - marine species

## TASKI TAPI DEFOAM

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (days)
Propan-2-ol		No data available			

Impact on sewage plants - toxicity to bacteria

Ingredient(s)	Endpoint	Value (mg/l)	Inoculum	Method	Exposure time
Propan-2-ol	EC <sub>50</sub>	> 1000	Activated sludge	Method not given	

**Aquatic long-term toxicity**

Aquatic long-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
Propan-2-ol		No data available				

Aquatic long-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
Propan-2-ol		No data available				

Aquatic toxicity to other aquatic benthic organisms, including sediment-dwelling organisms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw sediment)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

**Terrestrial toxicity**

Terrestrial toxicity - soil invertebrates, including earthworms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

Terrestrial toxicity - plants, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

Terrestrial toxicity - birds, if available:

Ingredient(s)	Endpoint	Value	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

Terrestrial toxicity - beneficial insects, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

Terrestrial toxicity - soil bacteria, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

**12.2 Persistence and degradability****Abiotic degradation**

Abiotic degradation - photodegradation in air, if available:

Ingredient(s)	Half-life time	Method	Evaluation	Remark
Propan-2-ol	No data available			

Abiotic degradation - hydrolysis, if available:

## TASKI TAPI DEFOAM

Ingredient(s)	Half-life time in fresh water	Method	Evaluation	Remark
Propan-2-ol	No data available			

Abiotic degradation - other processes, if available:

Ingredient(s)	Type	Half-life time	Method	Evaluation	Remark
Propan-2-ol		No data available			

**Biodegradation**

Ready biodegradability - aerobic conditions

Ingredient(s)	Inoculum	Analytical method	DT <sub>50</sub>	Method	Evaluation
Propan-2-ol			95 % in 21 day(s)	OECD 301E	Readily biodegradable

Ready biodegradability - anaerobic and marine conditions, if available:

Ingredient(s)	Medium & Type	Analytical method	DT <sub>50</sub>	Method	Evaluation
Propan-2-ol					No data available

Degradation in relevant environmental compartments, if available:

Ingredient(s)	Medium & Type	Analytical method	DT <sub>50</sub>	Method	Evaluation
Propan-2-ol					No data available

**12.3 Bioaccumulative potential**

Partition coefficient n-octanol/water (log Kow)

Ingredient(s)	Value	Method	Evaluation	Remark
Propan-2-ol	0.05	OECD 107	No bioaccumulation expected	

Bioconcentration factor (BCF)

Ingredient(s)	Value	Species	Method	Evaluation	Remark
Propan-2-ol	No data available				

**12.4 Mobility in soil**

Adsorption/Desorption to soil or sediment

Ingredient(s)	Adsorption coefficient Log K <sub>oc</sub>	Desorption coefficient Log K <sub>oc</sub> (des)	Method	Soil/sediment type	Evaluation
Propan-2-ol	No data available				Potential for mobility in soil, soluble in water

**12.5 Other adverse effects**

No other adverse effects known.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Waste from residues / unused products:**

The concentrated contents or contaminated packaging should be disposed of by a certified handler or according to the site permit. Release of waste to sewers is discouraged. The cleaned packaging material is suitable for energy recovery or recycling in line with local legislation.

**Empty packaging****Recommendation:**

Dispose of observing national or local regulations.

**Suitable cleaning agents:**

Water, if necessary with cleaning agent.

**SECTION 14: Transport information****ADG, IMO/IMDG, ICAO/IATA****14.1 UN number or ID number:** 1219**14.2 UN proper shipping name:**



## TASKI TAPI DEFOAM

Isopropanol (isopropyl alcohol) , solution

**14.3 Transport hazard class(es):**

Transport hazard class (and subsidiary risks): 3

**14.4 Packing group:** II**14.5 Environmental hazards:**

Environmentally hazardous: No

Marine pollutant: No

**14.6 Special precautions for user:** None known.**14.7 Maritime transport in bulk according to IMO instruments:** The product is not transported in bulk tankers.**Other relevant information:**

Hazchem code: +2YE

IMO/IMDG

EmS: F-E, S-D

This product has been classified, labelled and packaged in accordance with the requirements of the NZ Land Transport Rule: Dangerous Goods, ADG, and the provisions of the IMDG Code.

Transport regulations include special provisions for certain classes of dangerous goods packed in limited quantities.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002528.

**Group standard**

Cleaning Products (Flammable) Group Standard 2020

**Inventory Listing(s)**

New Zealand: NZIoC (New Zealand Inventory of Chemicals)

All components are listed on the NZIoC inventory, or are exempt

**HSNO Classification**

3.1B - Flammable liquid: high hazard

6.1E - Acutely toxic (oral)

6.3B - Mildly irritating to the skin

6.4A - Irritating to the eye

**SECTION 16: Other information**

*The information in this document is based on our best present knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally binding contract*

**SDS code:** MS32000445

**Version:** 01.1

**Revision:** 2023-11-30

**Reason for revision:**

1, Not applicable

**Exposure standards - Time Weighted Average (TWA) or Workplace Exposure Standard (WES) (NZ):** Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

**Abbreviations and acronyms:**

- DNEL - Derived No Effect Limit
- AUH - Non GHS hazard statement
- PNEC - Predicted No Effect Concentration
- ATE - Acute Toxicity Estimate
- LD50 - Lethal Dose, 50% / Median Lethal dose
- LC50 - Lethal Concentration, 50% / Median Lethal Concentration
- EC50 - effective concentration, 50%
- NOEL - No observed effect level
- NOAEL - No observed adverse effect level
- STOT-RE - Specific target organ toxicity (repeated exposure)
- STOT-SE - Specific target organ toxicity (single exposure)
- EC No. - European Community Number
- OECD - Organisation for Economic Cooperation and Development

**End of Safety Data Sheet**